

JOURNAL *of the*
BOSTON SOCIETY
OF
CIVIL ENGINEERS



124 YEARS
1848 - 1972

FLETCHER granite

for

Bridges and Buildings
Street and Highway Curbing

ASHLAR VENEER

for

Bridge Facing - Walls

Landscaping

* * *

Brochure will be mailed on request

* * *

H. E. FLETCHER CO.

Quarry and Office

WEST CHELMSFORD, MASSACHUSETTS 01863

Phone 617-251-4031

JOURNAL OF THE BOSTON SOCIETY OF CIVIL ENGINEERS

Volume 59

JULY 1972

Number 3

CONTENTS

Shear Wall-Frame Interaction <i>Stephen Chriss</i>	133
Removal of Agents from Wastewaters with Ozone <i>Jon Marquis Foulds</i>	151
Proceedings of the Society	160

Copyright, 1972, by the Boston Society of Civil Engineers
Second-Class postage paid at Boston, Massachusetts

Published four times a year, January, April, July and October, by the Society
230 Boylston Street, Boston, Massachusetts 02116

Subscription Price \$10.00 a Year (4 Copies)
\$2.50 a Copy
All orders must be accompanied by check

BOSTON SOCIETY OF CIVIL ENGINEERS

OFFICERS, 1972 – 1973

President

JAMES P. ARCHIBALD

Vice-Presidents

MAX D. SOROTA

(Term expires March 1973)

PETER S. EAGLESON

(Term expires March 1974)

Secretary

JOSEPH F. WILLARD

Treasurer

ROBERT T. COLBURN

Directors

CHARLES A. PARTHUM

LAWRENCE C. NEALE

(Term expires March 1973)

CHARLES C. LADD

CHARLES H. FLAVIN

(Term expires March 1974)

Past Presidents

ROBERT H. CULVER

ERNEST L. SPENCER

ERNEST A. HERZOG

Sanitary Section

JOHN J. COCHRANE, Chairman

WILLIAM H. PARKER, 3rd, Clerk

Structural Section

JURGIS GIMBUTAS, Chairman

HAROLD V. MCKITTRICK, Clerk

Transportation Section

ROBERT T. TIERNEY, Chairman

R. LAWRENCE WHIPPLE, Clerk

Hydraulics Section

JEROME DEGEN, Chairman

ROBERT S. RESTALL, Clerk

Construction Section

JOHN T. QUINN, Jr., Chairman

SAMUEL E. RICE, 3rd, Clerk

Geotechnical Section

EDMUND G. JOHNSON, Chairman

VINCENT J. MURPHY, Clerk

Computer Section

ROBERT D. LOGCHER, Chairman

CHARLES D. SHAKER, Clerk

JOURNAL EDITOR – H. HOBART HOLLY

230 Boylston Street – Room 714

Boston, Massachusetts 02116

**JOURNAL OF THE
BOSTON SOCIETY OF CIVIL ENGINEERS**

Volume 59

JULY 1972

Number 3

**A CASE STUDY OF
SHEAR WALL-FRAME INTERACTION**

by Stephen Chriss*

Abstract

A shear wall-frame system pertaining to an actual building has been investigated for deflection and rotation caused by wind loading. Computational means employed were a desk calculator, a wire model and a computer facility. The analysis method used, consisted of computing stiffness matrices for substitution into an equilibrium equation, which was subsequently solved for system deflections. The contribution of frames in reducing system deflections is significant.

Introduction

Composite shear wall-frame action due to lateral loading is characterized by considerably lower lateral deflections and shear wall rotations than would be obtained if the shear wall was acting alone. Although the principle of the above statement is generally understood and its validity accepted, data in the published literature indicating manifestations of interaction are scarce.

The present study was therefore undertaken in order to determine response characteristics for the system investigated, which possessed rather unusually high beam-to-column and shear wall-to-column stiffness ratios. A simple method of analysis is presented, aiming at determining deflections of the combined shear wall-frame system. Resultant rotations, as well as deflections and rotations for the shear wall acting alone are also presented for comparison. The investigation is of combined analytical-experimental nature and pertains to the Physics Tower of the University of Toronto.

The study was instigated by the necessity of determining whether the rotation of the top of the central core at the 16th floor level under moderate wind load was within the specified limits. Low rotation limits were required due to the operational characteristics of two astronomical telescopes mounted on the top of the core.

*Research engineer EDOK-ETER, Athens, Greece.

Building Characteristics

The building shown completed in Fig. 1 and in plan in Fig. 2 structurally consists of four supporting perimetric frames, a group of three interior columns and a central core, all interconnected through plane-rigid floor plates.

Perimetric frames and central core terminating at the fifteenth and sixteenth floor levels respectively, are supported at the basement level by a criss-cross wall type foundation, assumed to provide a perfectly flexurally rigid base for the purpose of the present analysis. The central core consists of reinforced concrete sections of 8, 12 and 16 in. in thickness, and reinforced as concrete columns at points of high stress such as corners and doorways. Concrete strength changes from 4 to 3 ksi at the 9th floor level.

Perimetric frames consist of 25-in. x 24-in. reinforced concrete columns and 6-ft 8-in. deep composite beams. Column concrete strength changes from 4 to 3 ksi at the 7th floor level. The composite beams consist of 3-ft 3-in. deep, 1-ft wide 3 ksi reinforced concrete spandrel beams supporting the floor plate, and 3-ft 5-in. deep, 8-in. concrete block panel; the latter is bonded to the spandrel beams with cement mortar and topped by cast in concrete 6 x 4 B 8.5 steel beams interconnecting adjacent columns as shown in Fig. 3. Steel beams were introduced as tension-compression members in order to mobilize into flexural action the full depth of the composite beam, thereby increasing the stiffness of perimetric frames. Stiff frames would in turn result in limited rotation at the top of the core as necessitated by the operational characteristics of the telescopes.

Floor plates consist of 15-in. deep stems and 3-in. thick deck concrete waffle type slabs.

The story height between the first basement level (at which frames and core meet the rigid foundation) and the first floor is 17.5 ft., that between first and second is 18.7 ft., and all remaining story heights are 12.9 ft.

Analysis of System

Method of Analysis

The system resisting lateral motion shown in Fig. 4 consists of a planar array of a frame element and a shear wall element, interconnected at floor levels through links. The above elements represent respectively (1) the combination of two opposite physical perimetric frames whose planes are parallel to the direction of wind, and (2) the physical central core.

Frames and central core are assumed fixed at the first basement floor level. The interconnecting links representing the concrete floor plates are assumed hinged at both ends and inextensible, i.e. not altering their length under the influence of interaction forces between the shear wall and frame elements.




Fig. 2. Floor Plan of Physics Tower




Fig. 1. University of Toronto Physics Tower




Fig. 3. Typical Column - Composite Beam Intersection




Fig. 4. System Resisting Lateral Loads

System deflections were determined from equilibrium considerations, from the expression:

$$([A^W] + [A^F]) \{u\} = \{F\} \dots\dots\dots 1$$

in which $[A^W]$ and $[A^F]$ are the square stiffness matrices for the shear wall and frame elements respectively, and $\{u\}$ and $\{F\}$ are the column matrices of system horizontal deflections and externally applied forces respectively. The above equation can be obtained by writing the well known stiffness matrix equation¹ for the shear wall and frame elements separately, and adding the two together.

Stiffness coefficients for the central core disregarding the effect of shear were determined as follows. One point at a time was deflected while all other points were locked against translation only; the stiffness coefficient A_{kj} is then equal to the reaction required to keep point k locked against translation, while a load applied at point j is producing a unit displacement at j . Reactions were determined from moment distribution. All arithmetical operations were carried out through a desk calculator rather than a slide rule due to the required accuracy in formulating the stiffness matrix. A constant flexural rigidity $EI = 2.30 \times 10^{10}$ kip-ft² was used in the calculations. This figure representing an average of the rigidities in the two building directions, was arrived at by conventional methods after due allowance for openings and doorways.

Stiffness coefficients for the perimetric frames were determined by means of a wire model as described further. Stiffness expressions for the central core (shear wall element) and the two perimetric frames combined (frame element) are given by Eqs. 2 and 3 below which indicate the nature of the coefficients rather than the complete coefficient layout.

An outline of the method of computation of rigidities is given in Appendix

I.

$$\left\{ \begin{matrix} P_1 \\ P_2 \\ P_3 \\ . \\ . \\ P_{14} \\ P_{15} \\ P_{16} \end{matrix} \right\} = \left[\begin{matrix} +43.855 & -31.842 & +16.911 & . & . & 0 & 0 & 0 \\ -31.866 & +53.571 & -52.095 & . & . & 0 & 0 & 0 \\ +16.921 & -52.100 & +82.156 & . & . & 0 & 0 & 0 \\ . & . & . & . & . & . & . & . \\ . & . & . & . & . & . & . & . \\ 0 & 0 & 0 & . & . & +84.566 & -56.536 & +14.930 \\ 0 & 0 & 0 & . & . & -56.537 & +57.697 & -20.786 \\ 0 & 0 & 0 & . & . & +14.934 & 20.787 & +9.010 \end{matrix} \right] \left\{ \begin{matrix} u_1 \\ u_2 \\ u_3 \\ . \\ . \\ u_{14} \\ u_{15} \\ u_{16} \end{matrix} \right\} \dots\dots\dots 2$$

$$\begin{Bmatrix} P_1 \\ P_2 \\ P_3 \\ . \\ . \\ P_{13} \\ P_{14} \\ P_{15} \end{Bmatrix} = \begin{bmatrix} +0.082 & -0.40 & 0 & . & . & 0 & 0 & 0 \\ -0.040 & +0.190 & -0.150 & . & . & 0 & 0 & 0 \\ 0 & -0.150 & +0.300 & . & . & 0 & 0 & 0 \\ . & . & . & . & . & . & . & . \\ . & . & . & . & . & . & . & . \\ 0 & 0 & 0 & . & . & +0.300 & -0.150 & 0 \\ 0 & 0 & 0 & . & . & -0.150 & +0.300 & -0.150 \\ 0 & 0 & 0 & . & . & 0 & -0.150 & +0.150 \end{bmatrix} \begin{Bmatrix} u_1 \\ u_2 \\ u_3 \\ . \\ . \\ u_{13} \\ u_{14} \\ u_{15} \end{Bmatrix} \cdot 3$$

In the above expressions, forces P are in kips and deflections u are in millionths of a foot.

It is noted from Eq. 3 that the frame element corresponds to a discrete spring type system², since the influence of deflecting a floor level is only spread to the floors above and below. Such an action is attributable to the fact that the ratio of composite beam to column stiffness is of the order of 10.

The lateral forces acting on the building were assumed to be those due to a 25 mph wind producing a pressure increasing with the floor level according to the recommendations of the National Building Code of Canada. The wind load was considered negligible up to the 50-ft. level (4th floor) due to the shielding effect of neighboring buildings.

Wire Model

Due to the nature of the composite beams, the columns were considered free to deform flexurally in their height corresponding to the depth of the block panel; in addition, the steel beam, its concrete encasement, and its tributary width of concrete block panel were considered to provide an elastic restraint to column lateral deflections. The above considerations, outlined in Appendix I, correspond to an idealized frame section as shown in Fig. 5. Resort, therefore, was made to a wire mechanical model for the determination of stiffness coefficients of the perimetric frames.

A typical wire model section representing the physical prototype section (Fig. 5) is shown in Fig. 6. Flexible arms A correspond to the springs of Fig. 5. Arms A offer elastic restraint to wires C through cantilever action, and were made effective through post-tensioning of a fine steel wire after soldering had been completed. Wire bands B and C correspond to the flexural rigidities of the prototype composite beam and column respectively and the gusset plate G corresponds to the column-spandrel beam poured joint.




Fig. 5. Idealized Typical Prototype Frame Section




Fig. 6. Wire Model - Typical Section Corresponding to Fig. 5

Model characteristics were prescribed by the scales of length $1/K_\ell$, stiffness $1/K_k$, and spring constant $1/K_s$. The first two scales were independently chosen, while $1/K_s$ is equal to K_ℓ^3/K_k as follows from similitude theory^{3,4}; $1/K_s$ is relating the elastic column restraint of the prototype (springs of Fig. 5) to the corresponding element of the model (flexible arms of Fig. 6.).

Numerical values of the scales were chosen on considerations of convenience of construction and loading, practicability of model size, availability of model members and readability of deflections; the values chosen were:

$$\frac{1}{K_\ell} = \frac{L_m}{L_p} = 0.025 \quad \dots\dots\dots 4$$

$$\frac{1}{K_k} = \frac{(EI)_m}{(EI)_p} = 0.555 \times 10^{-10} \quad \dots\dots\dots 5$$

$$\frac{1}{K_s} = \frac{C_m}{C_p} = \frac{K_\ell^3}{K_k} = 3.55 \times 10^{-6} \quad \dots\dots\dots 6$$

in which L, (EI) and C represent length, flexural rigidity and spring constant respectively, and the subscripts m and p apply to model and prototype respectively.

The model was constructed of spring temper wires jointed by means of non-creep solder. Since the frames were assumed to act essentially as discrete spring type systems, only five stories were incorporated into the model. This assumption was verified during experimentation by the fact that the stiffness coefficients for levels two stories away were 4 percent or less of the coefficients one story away from the loaded level.

Experimental arrangement and schematic representation are shown in Fig. 7 and 8 respectively. A simple electrical circuit was utilized to indicate contact of the model with the pins P, while the model was under the influence of weights placed on the trays.

The following technique was utilized. With the switches RS (regular) and MS (momentary) closed, enough weights were placed on tray T2 to just break the circuit between the pin and the model (light of bulb B off). Weights were then placed on tray T1 creating a deflection Δ , reestablishing the contact between pin and model. Counter-balancing weights W were then placed on tray T2 to just break again the contact. The stiffness coefficient A_{43} for model would then be equal to W/Δ . Two deflection operations were performed to test




Fig. 7. Wire Model — Experimental Arrangement




Fig. 8. Wire Model — Schematic Representation

the linearity of the $W-\Delta$ relationship, and the average W/Δ value was taken. The difference between the values obtained for each deflection operation was in most cases between zero and 7%. Deflections were measured on a scale graduated in hundredths of an inch and read through a magnifying glass.

System Solution

The expressions given by Eqs. 2 and 3 and the force vector given by the second column of Table 1 were combined into the form of Eq. 1 for the solution of which a digital computer facility was employed. Determined values of deflections u were then back-substituted into Eq. 3 to yield forces acting on the frame element. These forces were in turn subtracted from the externally applied loads, to yield the forces acting on the shear wall element. Force distribution and system deflections are shown in Table 1.

To check the correctness of the solution, the deflection of the shear wall element under the calculated set of forces was determined by cantilever deflection formulas and compared to the computer solution set of deflections: a very close agreement was obtained.

Table 1. System Forces and Deflections

FLOOR LEVEL	FORCES (KIPS)			SYSTEM HORIZONTAL DEFLECTIONS u (FEET)
	EXTERNALLY APPLIED FORCES F	ON SHEAR WALL ELEMENT FORCES P	ON FRAME ELEMENT FORCES P	
16	4.14	4.14	—	0.001948
15	4.54	-13.44	17.98	0.001824
14	4.36	4.12	0.24	0.001704
13	4.36	3.98	0.38	0.001583
12	4.36	3.85	0.51	0.001459
11	4.36	3.73	0.63	0.001307
10	4.36	3.74	0.62	0.001200
9	4.36	3.87	0.49	0.001063
8	4.36	4.01	0.35	0.000925
7	3.55	3.52	0.03	0.000783
6	3.47	3.95	-0.48	0.000642
5	3.47	4.46	-0.99	0.000503
4	0	1.63	-1.63	0.000373
3	0	2.35	-2.35	0.000253
2	0	11.29	-11.29	0.000148
1	0	2.78	-2.78	0.000038

Rotations at the top of the central core were obtained from the difference of horizontal deflections divided by the story height. For comparison, deflection, and rotation at the top of the central core if it were acting alone, were also computed from cantilever deflection formulas. Both sets of response characteristics are shown in Table 2.

Table 2. Comparison of Response Characteristics

SYSTEM	HORIZONTAL DEFLECTION AT TOP OF CORE (FEET)	ROTATION AT TOP OF CORE (RADIAN)
FRAME PLUS SHEAR WALL ELEMENTS	0.00195	0.92×10^{-5}
SHEAR WALL ELEMENT ONLY	0.00680	4.5×10^{-5}

Summary and Conclusions

A combined analytical-experimental approach to the problem of determining deflections of a shear wall-frame system has been outlined. Computational means employed were a desk calculator, a wire model and a computer facility for the determination of stiffness coefficients for the shear wall element, the frame element and system solution respectively. The above computational means could be interchanged or interreplaced.

Although the stiffness coefficients for the frame element are more than two orders of magnitude smaller than those for the shear wall element, the contribution of the former element has a marked effect on decreasing system response characteristics (Table 2).

References

1. Argyris, J.H. and Kelsey S., "*Energy Theorems and Structural Analysis*", Butterworths, London, Toronto, 1960, p. 22.
2. Could, P.L., "Interaction of Shear Wall-Frame Systems in Multistory Buildings", *Journal of the American Concrete Institute*, Vol. 62, Title 62-4, January 1965, pp. 45-70.
3. Hetenyi, M. "*Handbook of Experimental Stress Analysis*", John Wiley & Sons, New York, 1950, p. 693.
4. Chriss, S., "*Use of Models in Technical Studies*", B.A.Sc. Thesis, University of Toronto, Dept. of Civil Engineering, 1961, p. 16.

Appendix I

Outline of the Method of Computation of Rigidities

1. Central Core (Shear Wall Element)

Calculation of the moments of inertia of the central core of the building, was based on the following assumptions:

1. Plane sections before bending remain plane after bending, i.e. warping is absent.
2. Material over doorways does not contribute to stiffness.

Accordingly, the centroidal axis XX, was located by means of conventional methods for the cross section shown in Fig. A1. Axis YY is an axis of symmetry.

Subsequently the moments of inertia were evaluated for the cross section. Due to the first of the above mentioned assumptions, the calculated moment of inertia is overestimated, since during bending about the YY axis, in reality, sections such as ABC, DEF, G, H (Fig. A1) will not be fully effective due to warpage (Fig. A2). The same is true for bending about the YY axis.

Due to the second of the above mentioned assumptions, the calculated moments of inertia are underestimated, since in reality, the material existing over doorways will contribute to stiffness.

The two above mentioned opposite effects were considered to cancel each other at least partially, thereby resulting in a moment of inertia approaching the true condition.

The moments of inertia for the concrete alone were found as:

$$I_{XX} = 2.200 \times 10^4 \text{ ft}^4$$

$$I_{YY} = 2.346 \times 10^4 \text{ ft}^4$$

Taking into account the effect of vertical reinforcement by consideration of transformed steel areas:

$$\begin{array}{l} \text{0 to 9th floor} \\ I_{XX} = (2.200 + 0.200) \times 10^4 = 2.400 \times 10^4 \text{ ft}^4 \end{array}$$

$$I_{YY} = (2.346 + 0.200) \times 10^4 = 2.546 \times 10^4 \text{ ft}^4$$

$$\begin{array}{l} \text{9th to 15th floor} \\ I_{XX} = (2.200 + 0.140) \times 10^4 = 2.340 \times 10^4 \text{ ft}^4 \end{array}$$

$$I_{YY} = (2.346 + 0.140) \times 10^4 = 2.486 \times 10^4 \text{ ft}^4$$




Fig. A1. Central Core Plan Used in Evaluation of Moments of Inertia




Fig. A2. Central Core Flexural Deformations

The modulus of elasticity for concrete was taken as:

$$0 \text{ to } 9\text{th floor } (f'_c = 4 \text{ ksi}) : E = 5.3 \times 10^5 \text{ kip/ft}^2$$

$$9\text{th to } 15\text{th floor } (f'_c = 3 \text{ ksi}) : E = 4.8 \times 10^5 \text{ kip/ft}^2$$

Thus flexural rigidities become:

$$0 \text{ to } 9\text{th floor: } (EI)_{XX} = 1.24 \times 10^{10} \text{ kip-ft}^2, (EI)_{YY} = 1.35 \times 10^{10} \text{ kip-ft}^2$$

$$9\text{th to } 16\text{th floor: } (EI)_{XX} = 1.12 \times 10^{10} \text{ kip-ft}^2, (EI)_{YY} = 1.20 \times 10^{10} \text{ kip-ft}^2$$

Although the arithmetic average of the above figures is 1.23×10^{10} , the value used in assembling the stiffness matrix was: $EI = 1.30 \times 10^{10} \text{ kip-ft}^2$ since the bottom (stiffer) part of the cantilever, has a stronger influence on deflections than the top.


2. Perimetric Frames (Frame Element)

Calculation of rigidities of perimetric frames was based on the following considerations and assumptions:

1. Steel beam, encasing concrete, block panel and poured concrete, spandrel, Fig. A3, act integrally as a composite beam.
2. Concrete column-concrete block interfaces AB (Fig. A3) cannot develop either tensile or compressive forces. Therefore columns can deform flexurally in the lengths AB, the latter being physical gaps, as shown in Fig. 5.
3. Blocks AEDCA (Fig. A3) consisting of the steel beam, its concrete encasement and its tributary width of block panel act as elastic restraint for the column, when it (column) is laterally deflected. The extensional rigidity EA of the block divided by its length, i.e., its spring constant is that of a strut having length ED and cross-sectional area and modulus of elasticity, those corresponding to the middle position M .

For the evaluation of the flexural rigidity of the composite beam, the neutral axis was first located by considering transformed areas. The moduli of elasticity of poured concrete, concrete block and steel beam were taken in the ratios 1:0.5:10 respectively. Subsequently, the moment of inertia was calculated as $I = 19.3 \text{ ft}^4$; the corresponding flexural rigidity was then: $EI = 19.3 \times 4.7 \times 10^5 = 9.1 \times 10^6 \text{ kip-ft}^2$. The spring constant C_p of blocks AEDCA was calculated as:

$$C_p = \frac{\Sigma EA}{L} = \frac{I}{L} (E_1 A_1 + E_2 A_2 + E_3 A_3)$$



LEGEND

KP Composite Beam Consisting of:

1. Steel Beam
2. KL Concrete Encasement 1' - 1" Deep, 8" Wide
3. LN Concrete Block Panel 2' - 4" Deep, 8" Wide
4. NP Poured Concrete Spandrel 3' - 3" Deep, 12" Wide

ADECA — Elastic Restraint to column lateral deflection, consisting of concrete encasement, steel beam, tributary block panel shown shaded.

Fig. A3. Resisting Elements of Frame

where E_1A_1 , E_2A_2 , E_3A_3 refer to concrete encasement, steel beam, and concrete block respectively. Since $L = 4.8$ ft, $E_1 = 4.7 \times 10^5$ kip/ft², $E_2 = 10E_1$, $E_3 = 0.5E_1$, $A_1 = 0.72$ ft², $A_2 = 0.017$ ft², $A_3 = 0.60$ ft², the value of C_p becomes: $C_p = 1.16 \times 10^5$ kip/ft.

The flexural rigidities for the columns were calculated as follows:

0 to 7th floor

For the concrete $I_c = \frac{24}{12} = 1.33$ ft⁴; for the circular reinforcement $I_s = 0.17$ ft⁴; total moment of inertia $I_t = 1.33 + 0.17 = 1.50$ ft⁴.

For the concrete, $E = 5.2 \times 10^5$ kip/ft². Thus $EI = 1.50 \times 5.2 \times 10^5 = 8.06 \times 10^5$ kip-ft² per column.

7th to 15th floor

For the concrete $I_c = \frac{24}{12} = 1.33$ ft⁴; for the tied reinforcement $I_s = 0.33$ ft⁴; total moment of inertia $I_t = 1.33 + 0.33 = 1.66$ ft⁴.

For the concrete $E = 4.7 \times 10^5$ kip/ft². Thus $EI = 4.7 \times 1.66 \times 10^5 = 7.8 \times 10^5$ kip-ft² per column.

An average $EI = 7.9 \times 10^5$ kip-ft² per column was assumed throughout the height of the building.

Appendix II — Notation

A	=	stiffness coefficient;
$[A]$	=	square stiffness matrix;
C	=	spring constant = $\frac{f}{\delta}$;
EI	=	flexural rigidity;
F	=	external forces;
$\{F\}$	=	column matrix of external forces;
K_k	=	scale of flexural rigidities = $\frac{(EI)_p}{(EI)_m}$;
K_l	=	scale of lengths = $\frac{L_p}{L_m}$;
K_s	=	scale of spring constants = $\frac{C_p}{C_m}$;
L	=	length;
P	=	internal forces;
u	=	horizontal deflection;
$\{u\}$	=	column matrix of horizontal deflections;
W	=	weights loading model;

Greek Symbols

δ	=	axial deformation
Δ	=	model deflection

Superscripts

w	denotes shear wall
f	denotes frame

Subscripts

p	denotes prototype
m	denotes model

Key Words

Analysis, displacements, experimental, frame, investigation, shear wall, stiffness coefficients, system, wind load, wire model.

REMOVAL OF SURFACE ACTIVE AGENTS FROM WASTEWATERS WITH OZONE

by

Jon Marquis Foulds*

Introduction

The destructive oxidation of the anionic surfactant alkylbenzene-sulfonate (ABS) has been reported, but research about surfactant removal by frothing with oxidation is new. To effectively utilize the surfactants present in sewage for frothing, knowledge concerning surfactant destruction and removal from the liquid phase must be considered. This article discusses the reactivity and frothing of ABS and/or the linear alkylate sulfonate (LAS) with ozone.

Evans and Ryckman¹ stated that ozonization of secondary sewage effluent achieved reduction in the concentration of the anionic surfactant alkylbenzene-sulfonate (ABS), but frothing information was not reported. Buesher and Ryckman² stated that ozone is economical as a treatment method for removing ABS.

Sawyer³ showed that commercial alkyl benzene sulfonates were not readily degradable by the activated sludge process. The commercial variations of ABS (such as the new soft linear alkylate sulfonate — LAS) are rated with a higher value of biodegradability than ABS.

A series of experiments were performed to determine the removal process of ABS and/or LAS from the liquid phase of sewage. Experiments 2, 3, 4, 5, and 6 were compared with the Control Run-Experiment 1. Experiments 2, 3, 5, and 6 were performed to test the oxidation of biodegraded or partially oxidized LAS and/or ABS by ozone. The Experimental Methods section lists a description of each experiment.

The ozone reactor was a semibatch unit in which a gas passes continuously through the liquid contained in the reactor.

Experimental Methods

1. Reactions were run in the ozone reactor with only LAS solutions (the stock sample was an Interim Reference Sample from the American Soap and Detergent Association, Oct. 20, 1964). The LAS analysis was as follows: (a) LAS—60.8%, (b) Na_2SO_4 —36.1%, (c) free oil—0.4%, and (d) water—2.7%. The equivalent weight of the material was 348. The Infrared Method (IR) listed in Standard Methods was the test procedure for ABS and LAS, and the reactant for derivative preparation was 1-methyl heptyl amine. A very high concentration of

*Sanitary Engineer, Buck, Seifert & Jost, Consulting Engineers

LAS (1g/1) was added to the 3-liter glass reactor. A Welsbach Model T-23 ozone generator with oxygen feed having a capacity of 6 g/hour of ozone served as an ozone source. Approximately 45 mg of ferrous sulfate and manganous sulfate were added to the reactor.

2. An experiment was performed using effluent from the laboratory activated sludge system fed by a 5:1 ratio of glucose to yeast extract mixture and LAS (6mg/1). The predominant organisms in the biological reactor were paramecium, filamentous bacteria of the *sphaerotilus-Leptothrix* group (*Sphaerotilus Natans*), and nematodes.

3. An experiment was performed using concentrated sewage effluent from the Robert A. Taft Pilot Plant. The sewage effluent was concentrated by a factor of at least 5 by vacuum distillation. The ozonization period was seven hours.

4. An experiment was performed using a commercial detergent. The foam was not allowed to evolve from the vessel.

5. An experiment was performed using effluent from the laboratory activated sludge system fed by a 5:1 ratio of glucose to yeast extract with added detergent. The reactant was ozonated for 1 hour, *re-seeded* with fresh sewage and aerated for a longer period.


6. An experiment was performed using secondary sewage effluent. A part of the initial sample was filtered and evaporated to dryness. The material was redissolved in distilled water, filtered, and reevaporated to dryness. The ozone reaction froth was separated from the particulate material by centrifuging at 10,000 rpm and filtering through 0.47 micron millipore filter paper. The froth was evaporated to dryness, redissolved in distilled water, and reevaporated to dryness. Surface tension measurements were determined for the initial surfactant present and the surfactant present after ozonization.

Experimental Results

IR spectra of the LAS (1-methyl heptyl amine) derivative are shown in Figures 1 and 2. Figures, 3, 4, and 5 show the IR spectra of the detergent products from the ozonization reactions.

All of the tested extraction solutions showed the following phenomena: (a) the solutions were initially a dark orange-brown color, (b) the solutions sampled from the ozone reactor became light-yellow or clear as a function of the ozonization time, and (c) the recovered foamate extractions were a dark-orange brown color.

The IR spectra were identical (as a function of frequency of absorption) for all the samples. The IR spectra also indicated that the concentration of LAS in the foamate was greater than the concentration of LAS in the ozone reactor.



* traced from Perkin-Elmer paper (Part No. 337-1207)

Figure 1. Spectrum of LAS (1-methyl heptyl amine) Derivative




Figure 2. Spectrum of LAS (1-methyl heptyl amine) Derivative




Figure 3. Spectrum of LAS (1-methyl heptyl amine) Derivative




Figure 4. Spectrum of LAS (1-methyl heptyl amine) Derivative




Figure 5. Spectrum of LAS (1-methyl heptyl amine) Derivative

In the ozone semibatch reaction, a froth was produced within a short period of reaction time. The reaction gases, however, were in contact with the collapsed phase of foamate. The reactor was pre-aerated with oxygen for 30 minutes before the start of a reaction to determine if a froth would rise from the reactor. A slight frothing action was noticed, but the froth did not rise. The ozone stream was introduced into the reactor solution, which contained manganous and ferrous ions. These metal ions reacted with ozone.

A plot of surface tension versus concentration is shown in Figure 6. The curve is similar in appearance to the curve for ABS.

Figure 7 shows the region on the curves where COD/COD_0 plots as a horizontal line, demonstrating the first-order region of the curve. The initial COD reduction is rapid. With additional ozonization, reduction in COD of the tested sewage resulted at a slower rate.

Figure 8 shows that an ozonated sewage can be oxidized further by aerobic action. This result is of *great* concern to everyone concerned about toxicity in a water supply.

The importance of the frothing action in the COD reduction of wastewaters possessing detergents is shown in Figure 9. A very good mathematical description is summarized by Lemlich⁴.

Conclusions

No chemical oxygen demand (COD) reduction of LAS and/or ABS was detected in the series of experiments, and each experiment was replicable.

The infrared spectral analysis tests indicated that the surface active agent and/or agents in sewage during ozonization were replicable. All IR spectra were run from 4,000 to 1,500 cm^{-1} and from 1,300 to 400 cm^{-1} . Since product-spectra were identical to parent-structure-spectra, chemical oxidation is not suggested.

The significance of the testing is that a significant COD reduction of many domestic sewages is possible by oxidation and frothing with ozone⁵. It should be emphasized that the central treatment goal at a sewage treatment plant is separation and conversion by some process.

The fact that the LAS and/or ABS were not oxidized in the semibatch reaction system means that it could be recycled in a continuous ozone-frothing-reactor system, having added ferrous salts to stabilize the froth.




Figure 6. Plot of Surface Tension vs. Concentration




Figure 7. Laboratory Activated Sludge Effluent Feed (5:1 ratio of glucose to yeast extract with added detergent)




Figure 8. Laboratory Activated Sludge Effluent Feed (5:1 ratio of glucose to yeast extract with added detergent)




Figure 9. Detergent Behavior In Semibatch Reactor System

References

1. Evans, F.L. and Ryckman, D.W., "Ozonated Treatment of Wastes Containing ABS" presented at *18th Industrial Waste Conference*, Purdue Univ., Lafayette, Ind., 141 (1963).
2. Buesher, C.A. and Ryckman, D.W., "Reduction of Foaming of ABS by Ozonation" presented at *16th Industrial Waste Conference*, Purdue Univ., Lafayette, Inc. (1961).
3. Sawyer, C.N. and Ryckman, D.W., "Anionic Synthetic Detergents and Water Supply Problems", *Jour. Amer. Water Works Assn.*, 49, 4 (1957).
4. Lemlich, R., "Principles of Foam Fractionation", Chap. 1 in "Progress in Separation and Purification", Vol. 1, E.S. Perry, Ed., Interscience, New York, N.Y. (1968).
5. Foulds, J.M., Clark, J.W., and Donald B. Wilson, "Ozone Generated Froth For Sewage Treatment", *Water & Sewage Works*, March 1971.

Bibliography

- Adamson, A.W., *The Physical Chemistry of Surfaces*, 2nd Ed., Interscience, New York, N.Y., 1967.
- Rubin, Eliezer, Richard Everett, and Jacque Weinstock, "Contaminant Removal From Sewage Plant Effluents by Foaming", Public Health Service Publication No. 999-WP-5, U.S. Dept. of Health, Education and Welfare, Cincinnati, Ohio, Dec. 1963.
- American Public Health Association, American Water Works Association, and Water Pollution Control Federation, *Standard Methods For The Examination Of Water And Wastewater*, 11th Ed., Amer. Pub. Health Assoc., New York, N.Y. (1960).
- "Determination of Alkyl Benzene Sulfonates In Sewage" by American Soap & Glycerine Producers Report, *Jour. Water Pollution Control Federation*, 33, 85 (1961).
- Malaney, G.W., Sheets, W.D., and Ayres, J., "Surfactants And Tertiary Treatment Units", *Jour. Water Pollution Control Fed.*, 32, 11 (1960).
- Hansen, C.H., and Gotaas, H.B., "Sewage Treatment By Flotation", *Sewage Works Jour.*, 15, 242 (1943).
- Eldib, F.A., "Foam Fractionation For Removal Of Soluble Organics From Wastewater", *Jour. Water Pollution Control Fed.*, 33, 914 (1961).
- Subcommittee on Analytical Methods, Technical Advisory Committee, Association of American Soap and Glycerine Producers, Inc., "Determination Of Trace Amounts Of Alkyl Benzene Sulfonates In Water", *Ninth Annual Summer Symposium—Analysis of Industrial Wastes*, Vol. 28, No. 12, Dec. 1956, pp. 1822-1829.
- Foulds, J.M., "What's it all about? Algae", *Water And Waste Engineering*, August 1972, pp. 45-46.

PROCEEDINGS OF THE SOCIETY

Minutes of Meetings

Boston Society of Civil Engineers

May 31, 1972:— The regular meeting was held jointly with the Sanitary Section following the Section's Annual Outing, a tour of the Braintree incinerator and dinner at Valle's Steak House.

The meeting was called to order at 7 p.m. by Mr. Cochrane, Chairman of the Sanitary Section, who turned the meeting over to President Archibald for a few brief announcements.

Following a short business meeting chaired by Mr. Cochrane, he introduced the speaker, Mr. Frank L. Heaney of Camp-Dresser & McKee, who gave an interesting presentation with slides on the design and construction of the incinerator. After a question and answer period the meeting was adjourned at 9 p.m.

Seventy members and guests attended the meeting; 37 attended the dinner.

Joseph Willard
Secretary

Joint Meeting Of Structural and Computer Sections

May 10, 1972:— The Joint Meeting was called to order at 7:30 p.m., at Purcell's Restaurant by Jurgis Gimbutas, Structural Section Chairman. Fifty people were present.

Joseph F. Willard, Secretary of the Boston Society of Civil Engineers announced the relocation of Society Headquarters.

Robert D. Logcher, Computer Section Chairman, next made a few announcements.

Rubin Zallen, Vice Chairman of the Structural Section, introduced the members of the Executive Committee of the Section and made introductory remarks for the technical program "Practical Problems Using Computers In Structural Design", which was presented in two parts. Mr. Zallen introduced the speakers for each part.

Paul Goldberg of Albert Goldberg & Associates spoke on time sharing, and described many small design problems as well as a moderately sized three-dimensional problem.

Chan Lin and Tom Collins, both of Sepp Firnkas Engineering spoke on batch processing and described the design of a large project in Greece which was designed for earthquake loading.

After a question period, the meeting was adjourned at 9:15 p.m.

Respectfully submitted,

Harold V. McKittrick
Clerk, Structural Section

ALBRIGHT & FRIEL INC.

CONSULTING ENGINEERS

Water, Sewage, Industrial Wastes and Incineration Problems, City Planning Highways, Bridges and Airports, Dams, Flood Control, Industrial Buildings, Investigations, Reports, Appraisals and Rates

**THREE PENN CENTER PLAZA
PHILADELPHIA 2, PA.**



ANDERSON-NICHOLS & Company, Inc.

A COMPREHENSIVE ENGINEERING AND MANAGEMENT SERVICE

Consulting Engineers

Boston Concord Hartford
Massachusetts New Hampshire Connecticut

THE AUSTIN COMPANY

Designers • Engineers • Builders

★ ★ ★

General Offices: Cleveland, Ohio 44121
Offices in principal cities of North America,
Europe, South America and Australia
Wellesley Hills, Mass. 02181 Tel. (617) 237-1438

BARNES ENGINEERING COMPANY, Inc.

Civil Engineers

411 Lexington Street

AUBURNDALE, MASS. 02166



Brown & Root, Inc.

Engineers/Constructors/Houston, Texas

P. O. Box 3
Houston, Texas 77001
(713) 672-3011

A HALLIBURTON Company

CAMP DRESSER & McKEE

Consulting Engineers

Water Resources — Water & Air Pollution
Water Works — Water Treatment
Sewerage — Wastes Treatment
Refuse Disposal — Flood Control
Research & Development



One Center Plaza, Boston, Mass. 02108

ANDREW CHRISTO, Engineers

CONSULTING ENGINEERS

230 Boylston Street

Boston, Mass. 02116

Tel. 266-2525

CLARKESON & CLOUGH ASSOCIATES

Consulting Engineers

Design, Construction Inspection
Airports, Bridges, Tunnels, Highways,
Traffic and Transportation Analyses and
Reports, Valuations.

40 Washington St., Wellesley Hills,

BARNES & JARNIS, INC.

Engineers

61 BATTERYMARCH ST.
Boston, Mass. 02110

Tel. 542-6521 — Area Code 617

Congdon, Gurney & Towle, Inc.

Engineers

53 State Street

Boston, Mass.

BRASK AND STANDLEY ENGINEERING CO.

Consulting Engineers

177 State Street, Boston
227-3170

CRANDALL DRY DOCK ENGINEERS, Inc.

Dry Docks — Piers — Waterfront Structures
Underwater Examination

238 Main Street Cambridge, Mass.

William S. Crocker, Inc.
(Formerly Asplawall & Lincoln)

Registered Professional Engineers
Registered Land Surveyors

35 Wm. T. Morrissey Blvd., Boston, Mass. 02125

EUSTIS ENGINEERING CO.
Soil and Foundation Consultants

Soil Borings Laboratory Tests
Foundation Analyses and Reports

3011 28th ST. P. O. BOX 125
METAIRIE, LOUISIANA 70004

E. D'APPOLONIA
Consulting Engineers, Inc.

Foundation Engineering
Vibrations & Soil Dynamics
Applied Mechanics

ENGINEERING OFFICES
10 Duff Road M. R. 522B
Pittsburgh, Pa. 15235 Chesterton, Ind. 46304
(412 - 242-5107) (219 - 926-3814)
CORPORATE OFFICE
1177 McCully Drive, Pittsburgh, Pa. 15235

**FAY, SPOFFARD &
THORNDIKE, INC.**

**Engineering
for**

Public Works and Industry

11 Beacon Street, Boston, Mass. 02108

**De Leuw, Cather
&
Company**
Engineers


Public Transit — Traffic — Parking
Highways — Subways — Railroads
Community Planning — Urban Renewal
Municipal Works — Port Development

24 SCHOOL STREET
BOSTON, MASS. 02108

HARRY R. FELDMAN, INC.

Civil Engineers and Land Surveyors
Engineering and Survey Service for
Consulting Engineers - Architects
Contractors - Appraisers
Municipalities

Accolon Way Boston, Mass. 02114



RICHARD J. DONOVAN, INC.

ENGINEERS: Design & Construction Management
540 MAIN ST., WINCHESTER, MASS. 01890

Ganteaume & McMullen
Engineers

99 Chauncy Street

BOSTON

B. M. DORNBLATT & ASSOCIATES, INC.
Consulting Engineers

826 Lafayette Street, New Orleans, Louisiana
Atlanta Baton Rouge Gulfport

Highways—Bridges—Structures
Sewerage—Water Supply—Drainage
Commercial & Industrial, Site Development
Port Development—Marine Structures
Airports—Public Works—Railroads
Design—Reports—Valuations

GERAGHTY & MILLER, INC.

Consulting Ground-Water Hydrologists
Water Supply-Quality and
Pollution Problems
Regional Ground-Water Studies
Recharge-Well Design

44 Sintsink Drive East
Port Washington, N.Y. 11050
516-883-6760

Jacksonville, Fla. Hartford, Conn.
Ponce, P. R.



**EDWARDS
and KELCEY**

Engineers and Consultants

470 Atlantic Ave., Boston, Mass.

Field
Laboratory
Analytical Studies
in Soil Mechanics &
Geotechnical Engineering

**GOLDBERG-ZOINO
& Associates, Inc.**

SOIL AND FOUNDATION ENGINEERS

377 ELLIOT STREET, NEWTON UPPER FALLS, MASS. 02164

Greeley and Hansen
Engineers

Water Supply, Water Purification,
Sewerage, Sewage Treatment, Flood
Control Drainage, Refuse Disposal

222 S. Riverside Plaza, Chicago, Ill. 60606
233 B'way, New York, New York 10007

J. F. HENNESSY
Civil Engineer

BROOKLINE, MASS. 02146

4 CYPRESS STREET

566-3860

GREEN ENGINEERING AFFILIATES
Consulting Engineers
Water Supply and Treatment
Sewage and Industrial Waste Treatment
Storm Drainage Systems and Sanitary Sewers
Highways, Bridges & Structures

625 McGrath Highway

Winter Hill Branch

Boston, Massachusetts

617 623-2311

**HOWARD, NEEDLES,
TAMMEN & BERGENDOFF** **HNTB**
Consulting Engineers

Airports, Bridges, Structures
Foundations, Express Highways,
Water Resources

Suite 3050, Prudential Center

Boston, Massachusetts 10019

1345 Avenue of the Americas

New York, New York 10019

HALEY & ALDRICH, INC.
Consulting Soil Engineers

Site Investigations; Soil Mechanics Studies
for Foundations, Retaining Walls, Dams,
Highways, Airfields and Marine
Structures

Office and Laboratory

238 MAIN ST. CAMBRIDGE, MASS. 02142

JOHN J. KASSNER & CO., INC.
Consulting Engineers

475 PARK AVENUE SOUTH

NEW YORK, N. Y., 10016

(212) 685-8511

Haley and Ward

Civil and Sanitary Engineers

25 Fox Road - Waltham, Mass. 02154

Tel. 890-3980 Area Code 617

FENTON G. KEYES ASSOCIATES

Consulting

ARCHITECT-ENGINEERS

PROVIDENCE, R.I. 02903

WETHERSFIELD, CONN. 06109

WALTHAM, MASS. 02154

NASHUA, N.H. 03060

PUTNAM, CONN. 06260

The Haller Testing Laboratories Inc.

*Testing, Inspection of Structural
Materials, Concrete, Asphalt &
Soils and Structural Steel.*

Laboratories in New York, New Jersey,
Connecticut, Rhode Island and Water-
town, Massachusetts

68 Laurel St., Watertown, Mass. 02172

Tel. 924-2321

CHARLES A. MAGUIRE & ASSOCIATES INC.

CONSULTING ENGINEERS
& ARCHITECTS



Water Supply • Sewerage • Drainage • Solid Wastes

Highways • Bridges • Airports

Commercial and Industrial Buildings

Waterfront Facilities • Dams

Reports • Design • Supervision

BOSTON • PROVIDENCE • WETHERSFIELD • CARACAS

Hardesty & Hanover
Consulting Engineers

Bridges, Special Structures

Highways & Streets

Heavy Machinery, Sewers, Pipelines

Electrical Controls, Lighting,

Soil Mechanics & Foundations

Design - Reports - Inspection

101 Park Ave. New York, N.Y. 10017

MAIN

CHAS. T. MAIN, INC.

Engineers

Studies, Reports • Design • Construction Management

Southeast Tower, Prudential Center, Boston, Mass. 02116, Tel. (617) 262-3200
1301 E. Morehead St., Charlotte, North Carolina 28204, Tel. (704) 375-3761

**METCALF & EDDY | ENGINEERS**

STATLER BLDG., BOSTON • 423-5600

Alonzo B. Reed, Incorporated**CIVIL — MECHANICAL —
ELECTRICAL ENGINEERING**Planning for Industry — Utilities —
MunicipalitiesBoston, Massachusetts
Manchester, New Hampshire**H. W. MOORE ASSOCIATES***Consulting Engineers*Civil — Structural — Sanitary
Urban Planning and Transportation112 SHAWMUT AVENUE Tel.
BOSTON, MASS. 02118 357-8145**Maurice A. Reidy Engineers****101 Tremont Street**

Boston, Massachusetts 02108

**MUESER, RUTLEDGE,
WENTWORTH & JOHNSTON**
*Consulting Engineers*Foundations for Buildings, Bridges and Dams;
Tunnels, Bulkheads, Marine Structures; Soil
Studies and Tests; Reports, Design
and Supervision.415 Madison Avenue
New York, N. Y. 10017
Eldorado 5-4800**ROBERT M. RUMPF
& ASSOCIATES***Consulting Engineers
Structural & Civil*229 Berkeley Street
Copley 7-2656 Boston, Mass.**New England Survey Service Inc.***Civil Engineers & Land Surveyors***FIRST ORDER SURVEYS
GEODETIC SURVEYS**Property - Right of Way - Land Court - Topo-
graphic - Photogrammetric Surveys. Aerial Photo-
graphs - Vertical or Oblique.35 Wm. T. Morrissey Boulevard, Boston, Mass.
Tel. -287-105761 Arrow Road, Wethersfield, Conn., 06109
Tel. 203-563-9301**STORCH ENGINEERS**Florham Park Hartford Boston
New Jersey Connecticut Massachusetts**PARSONS, BRINCKERHOFF
QUADE & DOUGLAS***Engineers***STUDY • PLANNING • DESIGN**Highways • Bridges • Tunnels • Ports &
Harbors • Rapid Transit • Parking • Dams
Flood Control • Water Supply • Sewerage
Industrial Wastes • Buildings

711 Boylston St. Boston, Massachusetts

THE THOMPSON & LIGHTNER CO., INC.*Engineers*Designs and Engineering Supervision
Investigations, Testing and
Inspection of Structural Materials
Concrete, Asphalt, Soils Control

Offices and Laboratory, 8 Alton Place, Brookline 46, Mass

**HERMAN G. PROTZE
MATERIALS TECHNOLOGIST**36 Jaconnet Street
Newton Highlands, Mass.TESTING INSPECTION RESEARCH
DEVELOPMENT CONSULTATION**tibbetts engineering corp.**CONSULTING ENGINEERS
CIVIL / SANITARY / STRUCTURAL

620 BELLEVILLE AVE. / NEW BEDFORD, MASS. 02745

TEL. (617) 996-5633

**CHARLES R. VELZY
ASSOCIATES, INC.**

Consulting Engineers
Water Pollution Control
Industrial Wastes - Drainage
Solid Waste Disposal - Air Pollution
Control - Water Supply

350 Executive Blvd. | Mineola, N.Y. 11501
Elmsford, N.Y. 10523 | Babylon, N.Y. 11702

FRANK H. WHELAN, INC.

Consulting Engineers

**Bridges Buildings
Appraisals Investigations**

1616 SOLDIERS FIELD ROAD
BOSTON, MASS. 02135
Phone 254-9011

**JOSEPH S. WARD and ASSOCIATES
CONSULTING ENGINEERS**

Engineering Geology Earthworks
Soils and Foundations Reclamation
Retaining and Waterfront
Structures Pavements

91 Roseland Avenue,
Caldwell, New Jersey 07006
Telephone: 201-226-9191



WHITMAN & HOWARD, INC.
ENGINEERS & ARCHITECTS

89 BROAD STREET, BOSTON, MASS 02110
TEL. (617) 426-6400

**WESTON & SAMPSON
Sanitary-Civil
Consulting Engineers**

Water Supply, Treatment, Distribution
Sewerage, Sewage & Industrial Wastes
Treatment, Supervision of Treatment
Water & Air Pollution Studies—Rates
Drainage Flood Control Refuse Disposal

10 High Street Boston, Mass. 02110
Kellogg Road Essex Jct. Vt. 05452



**WOODWARD-CLYDE CONSULTANTS
AFFILIATED FIRMS**

GEOTECHNICAL ENGINEERING

WOODWARD-LUNDGREN & ASSOCIATES
SAN FRANCISCO OAKLAND SAN JOSE
ANCHORAGE
WOODWARD Mc NEILL & ASSOCIATES
LOS ANGELES ORANGE
WOODWARD CLEVELAND & ASSOCIATES
SAN DIEGO

WOODWARD WOODHOUSE & ASSOCIATES, INC.
NEW YORK CLIFTON NEW JERSEY
WOODWARD GARDNER & ASSOCIATES, INC.
PHILADELPHIA WASHINGTON D.C.
WOODWARD CLEVELAND & ASSOCIATES, INC.
DENVER
WOODWARD McMASTER & ASSOCIATES, INC.
KANSAS CITY ST. LOUIS OMAHA



SHANNON & WILSON, INC.

Soil Mechanics and Foundation Engineers

Engineering Geology and Geophysics
Field Exploration • Soils Laboratory
Instrumentation • Rock Mechanics
Seattle • Spokane • Portland • San Francisco



C-1 Clip . . . For Steel Column or Pile Splice.



K-3 Clip . . . Fixed Position Manual Adjustment.



E-3 Seats . . . fit all clips.

New construction method cuts cost

15%


**JUST CLIP
THE FRAME
TOGETHER
AND WELD**

- NO NOISE
- NO HOLES
- NO EXPENSIVE FABRICATING EQUIPMENT

Why not give the Owner a break in these days of high building costs. Why not abandon the horse and buggy days of a bolted steel structure and reinforced concrete. Why not use our Method for building an all welded one piece steel structure to save 15% on cost of bolted steel or 5% of cost of reinforced concrete.

Buy 10th Edition Saxe Structural Welding Manual,

Pocket size 120 pages, result of 40 years experience for design and construction of thousands of structures. Contents—Specifications, 8 pages; Design data, 42 pages; Design tables, 9 pages; Connection Details and Drawings, 47 pages; Photo illustration. 130 Work covered, High Rise Buildings, Beams, Columns, Pipe and Rectangular Tube sections, Trusses, Plate girders, Plate work.



MERCY HOSPITAL
Taylor & Fisher, Architect
Baltimore, Md.




Price

\$1.00

SAXE WELDED CONNECTIONS Eng.
1701 ST. PAUL ST. BALTIMORE, MD. 21202

Thousands of these Manuals have been sold. Why use it for a reference book when so many have used it to build one piece economical steel structures.



Most Complete Stock of **SURVEYORS' • BUILDERS' • ENGINEERS'** **INSTRUMENTS and ACCESSORIES**

SALES and REPAIRS

Theodolites • Transits • Levels • Rods
Tapes • Rules • Measuring Wheels

PRODUCTS OF ALL LEADING MANUFACTURERS : MODERN REPAIR DEPARTMENT

KERN LIETZ BERGER CURTA ROLATAPE	KOH-I-NOOR DAVID WHITE PATH SOKKISHA KUKER-RANKEN	DIETZGEN GURLEY WATTS LENKER LUFKIN	: Complete facilities for repair and collimation of almost any type of Engineers' and Builders' instrument.
--	---	---	---

Tel. 617-864-4840

**RENTALS OF LATE MODEL
TRANSITS and LEVELS**



CARL HEINRICH COMPANY
711 Concord Ave. • Cambridge, Mass. 02138

WEST END IRON WORKS

CAMBRIDGE, MASSACHUSETTS

STRUCTURAL STEEL

FOR

BRIDGES AND BUILDINGS

FRANKI

foundation specialists

PRESSURE INJECTED FOOTINGS
CAST-IN-PLACE PILES • CAISSONS
STRUCTURAL WALLS AND CUT-OFFS BY SLURRY TRENCH PROCESS

FRANKI FOUNDATION COMPANY

916 STATLER OFFICE BUILDING • BOSTON, MASSACHUSETTS 02116 • PHONE (617) 426-4369

Please mention the Journal when writing to Advertisers

WARREN BROTHERS COMPANY

Division of
ASHLAND OIL INC.

Massachusetts District Office

**430 Howard Street
Brockton, Mass. 02402**

Tel. 588-3660

CRUSHED STONE

BITUMINOUS CONCRETE

SPENCER, WHITE & PRENTIS, INC.

CONTRACTORS AND ENGINEERS


21 FRANKLIN STREET

QUINCY, MASS. 02169


TELEPHONE 773-9245

foundations
underpinning
drilled-in caissons
heavy construction
pretest tie-backs

MAIN OFFICE: NEW YORK
BRANCHES: DETROIT • CHICAGO • SAN FRANCISCO • WASHINGTON, D.C.



**Complete soil investigation service
anywhere in New England and the
eastern states.**



**Special equipment for islands
and other water areas.**

ATLANTIC TEST BORING CO., INC.

P. J. Maloney, Proprietor

34 KING STREET

BOSTON, MASS. 02122

**Foundation test borings
Undisturbed samples
Rock core drilling**

**Phone:
617 - 436-8428
617 - 436-8429**

Please mention the Journal when writing to Advertisers

**CARR-DEE TEST BORING
AND CONSTRUCTION CORP.**

*Complete Soil Investigation Service
Anywhere in New England*

**37 LINDEN ST.
MEDFORD, MASS. 02155**

**Phone:
617 - 391-4500**

Telephone COLUMBIA 5-2600

BEACON PIPING COMPANY

Power Plant Piping - High Pressure Piping

Fabricators of Piping

**205 FREEPORT STREET
DORCHESTER, MASS. 02122**

**SOIL INVESTIGATIONS
FOUNDATIONS**

**CONSTRUCTION
CENTRILINE**

RAYMOND INTERNATIONAL INC.

**74 Concord Street
North Reading, Mass. 01864**

Telephone: (617) 729-8105

Please mention the Journal when writing to Advertisers

HUB FOUNDATION CO., INC.

Telephone 617-237-9510

47 RIVER STREET, WELLESLEY, MASSACHUSETTS 02181

P I L E D R I V E R S

PIPE — SHEETING

WOOD — H-BEAMS

**C. L. GUILD DRILLING
& BORING CO., INC.**

Complete soil investigation service

P. O. Box 108 — Bodwell Street — Avon Industrial Park
AVON, MASSACHUSETTS 02322

Telephone Area Code 617 584-0510

NORTHEAST TEST BORING CO., INC.

DIAMOND DRILLING

"THE BEST FROM TOP TO BOTTOM"

FREE ESTIMATES

Tel. 471-0728 — 0729

156 ESSEX STREET

WEYMOUTH, MASS.

New England Concrete Pipe Corp.

NEWTON UPPER FALLS, MASSACHUSETTS

(617) 969-0220

MANUFACTURERS OF

Plain and Reinforced Concrete Sewer and Culvert Pipe

Pre-cast, Pre-stressed Concrete Structural Units

PLANTS

Newton, Dedham, Westfield, Plainville, Massachusetts

P. Gioioso & Sons, Inc.

GENERAL CONSTRUCTION

38 ROBINSON STREET

DORCHESTER

MASSACHUSETTS 02122

PIPE FOUNDERS SALES CORP.

CAST IRON AND DUCTILE IRON PIPE AND FITTINGS

Representing

The American Cast Iron Pipe Company

6 PLEASANT STREET MALDEN, MASSACHUSETTS 02148

617-324-3920

NEW ENGLAND FOUNDATION CO., INC.

Foundation Contractors

376 BOYLSTON STREET

BOSTON 16, MASS.

CAISSONS

**DRILLED
BELL BOTTOM
UNDERREAMED PIERS
DRIVEN**

PILING

**WOOD
COMPOSITE
CONCRETE
STEEL**

McKIE LIGHTER COMPANY

HINGHAM STREET

ROCKLAND, MASSACHUSETTS 02370

TEL: 617-871-1700

Hayes.....*the*
railroads' standard

BUMPING POSTS
 All-Steel,
 Universal fit,
 Six Types



DERAILS
 Sliding
 Hinge
 Portable



WHEEL STOPS
 Cushion® - Rigid - Skate




Free leatherette ring-binder catalog of world's most-specified derails, bumping posts and wheel stops (including periodic supplement sheets). Write on letterhead.

Specialists since 1903 in side track security
Hayes Track Appliance Co.
 RICHMOND, INDIANA 47374

**WHY
 WAIT
 ?**
instant printing

**THE
 ANSWER PEOPLE
 printing problem solvers**



157 High Street, Boston, Mass. 02110
 downtown — Phone: 423-3167

320 Stuart Street, Boston, Mass. 02116
 uptown — Phone: 426-1160

2089 Mass. Ave., Cambridge, Mass. 02140
 Cambridge — Phone: 492-6796

Vive la difference!

BOSTON SOCIETY OF CIVIL ENGINEERS

COMMITTEES 1972-1973

NOMINATING COMMITTEE

Harry L. Kinsel

John M. Biggs
Stephen M. Dore, Jr.
David A. Duncan
Howard Simpson
(Term expires 1973)

Harl P. Aldrich, Jr.
Leland F. Carter
Arthur H. Mosher, Jr.
Allan Grieve, Jr.
(Term expires 1974)

PROGRAM COMMITTEE

James P. Archibald, Chairman
John J. Cochrane
Jurgis Gimbutas
Robert T. Tierney

Max D. Sorota
Joseph F. Willard
H. Hobart Holly

John T. Quinn, Jr.
Edmund G. Johnson
Robert D. Logcher
Jerome Degen

PUBLICATION COMMITTEE

Peter S. Eagleson, Chairman
William A. Henderson
Simon Kirshen
John T. Quinn, Jr.
Edmund G. Johnson

H. Hobart Holly
John J. Cochrane
Jurgis Gimbutas
Robert T. Tierney

Robert D. Logcher
Max D. Sorota
James P. Archibald
Jerome Degen

LIBRARY COMMITTEE

Robert H. Culver, Chairman

Robert L. Fuller

HOSPITALITY COMMITTEE

Peter K. Taylor, Chairman

Conrad Fagone
Charles E. Fuller

MEMBERSHIP COMMITTEE

William S. Zoino, Chairman
A. Paul LaRosa
Edmund G. Johnson

Gerald L. Woodland, Jr.
David A. Duncan

Philip A. Bianchi
Samuel E. Rice, 3rd

Charles H. Flavin
Richard F. Battles

ADVERTISING COMMITTEE

William H. Parker, 3rd Chairman
Ronald E. Bucknam

H. Hobart Holly

Samuel E. Rice, 3rd

QUARTERS COMMITTEE

Max D. Sorota, Chairman

Robert H. Culver
Robert T. Colburn

David A. Duncan

BY-LAWS COMMITTEE

Paul A. Dunkerley, Chairman
Edward C. Keane

Robert T. Colburn
Max D. Sorota

Joseph F. Willard
Frank L. Heaney

JOHN R. FREEMAN FUND

Leslie J. Hooper, Chairman

David R. Campbell
George R. Rich

Lee M. G. Wolman
Harry L. Kinsel

RALPH W. HORNE FUND

William L. Hyland, Chairman

George G. Bogren

Harl P. Aldrich, Jr.

THOMAS R. CAMP FUND

Robert H. Culver, Chairman

John J. Cochrane

Jerome Degen

FITZGERALD-HERSCHEL AWARD

Peter S. Eagleson, Chairman

Edward C. Keane

Saul Namyet

SANITARY SECTION AWARD

Robert L. Meserve, Chairman

William C. Traquair

Charles Y. Hitchcock, Jr.

STRUCTURAL SECTION AWARD

Richard C. Jasper, Chairman

Robert L. Fuller

Frank J. Heger

TRANSPORTATION SECTION AWARD

H. Lowell Crocker, Chairman

Charles D. Shaker

Edward C. Keane

HYDRAULICS SECTION AWARD

Lawrence C. Neale, Chairman
Allan Grieve, Jr.

Lee M. G. Wolman

Allan T. Gifford

CONSTRUCTION SECTION AWARD

Paul S. Crandall, Chairman

William E. Wiley

Frank J. Killilea, Jr.

GEOTECHNICAL SECTION AWARD

Donald T. Goldberg, Chairman

Harl P. Aldrich, Jr.

Steve J. Poulos

COMPUTER SECTION AWARD

Frank E. Perkins, Chairman

Gerald L. Woodland, Jr.

Charles L. Miller

JOINT LEGISLATIVE COMMITTEE

Charles A. Parthum, Chairman
Ralph M. Soule

Joseph C. Knox

Cornelius J. O'Leary

SUBSOILS OF BOSTON COMMITTEE

Donald T. Goldberg, Chairman

Richard F. Battles
Edmund G. Johnson

Rev. Daniel Linehan
Ronald C. Hirschfeld

PUBLIC RELATIONS COMMITTEE

Walter Newman, Chairman
Saul Namyet

Peter S. Eagleson

Charles H. Flavin

AUDITING COMMITTEE

Charles C. Ladd

Lawrence C. Neale

INVESTMENT COMMITTEE

Robert T. Colburn, Chairman

Max D. Sorota

James P. Archibald

NEWSLETTER COMMITTEE

Bertram Berger, Chairman
Leonard J. Barberi


Peter Riordan

Robert T. Tierney

acker

"DRILLING EQUIPMENT
SPECIALISTS"
KNOWN ROUND THE WORLD

THE ACKER DRILL COMPANY manufactures a complete line of exploration drilling equipment such as Diamond Core Drills - Rotary Earth Augers - Soil Sampling Tools - Diamond Bits and Core Barrels - Tie Back Drills - Caisson Drills - Drilling Accessories and Supplies.



ACKER SOIL SAMPLING KIT

Unequaled collection of tools for recovering samples from practically any materials except rock. Hand carrying case included. Write for Bulletin No. 26.



ACKER MOTORIZED CATHEAD

Aluminum derrick with sheave and gasoline driven cathead hoist. Ideal for soil sampling - driving casing pipe - piezometer work standard penetration tests - Write for Bulletin No. 20.



ACKER "ACE" Core Drill

The Ace is a tried and proven core drill with unlimited versatility to perform a host of jobs. Ideal for truck, trailer or skid operation. Write for Bulletins No. 24 and 34.




ACKER VANE SHEAR

The vane shear is available in a torque head kit or hand torque kit. Assembly designed for obtaining accurate in-place shear values of cohesive soils - on the spot. Write for Bulletin No. 700.



ACKER DENNISON CORE SAMPLER

(Patented - No. 2,403,002) - Acker Dennison Soil Sampler - ideal for taking undisturbed quality cores from rare earths, ceramic clays, soft and difficult formations accepted by mining and soil engineers around the world. Write for Bulletin No. 1100.



ACKER "AUGER"

This AD 11 mechanical auger is ideal for soil sampling, earth augering, mineral prospecting and diamond core drilling - 8 rotation speeds and 6,725 ft. lbs. torque.

FREE

Acker has available free of charge a complete catalog on soil and rock exploration tool and equipment. Write for Acker catalog.

ACKER DRILL CO., INC., P.O. Box 830, Scranton, Pennsylvania 18501